

# Material Safety Data Sheet ULTRAMELT 3001

31/05/2018 : Update

1. Chemical Product And Company Identification	1.	Chemical	<b>Product And</b>	Company	Identification
--	----	----------	--------------------	---------	----------------

Product Name	Ultramelt 3001		
Product Type	Hot Melt Adhesive		
Suggested purpose and limitations	Bonding, adhesion		
Company Name	Nordale Australia Pty Ltd (ABN 66 114 879 122)		

#### 2. Hazardous Identification

211102010005100111110011	
Hazardous Category	Non-hazardous substances
GHS label	None
Label Content	
Symbol	None
Warnings	Do not touch it directly while melting by heat to avoid scalding
Hazard warning message	Touching it directly while melting by heat will cause contact burns.
Hazard prevention measures	None
Other hazards	None

## 3. Composition, Information On Ingredients

Mixture		
Ingredients	CAS No.	WT%
Polyolefin	9010-79-1	35 ~ 45%
Hydrogenated hydrocarbon	69430-35-9	35 ~ 45%
Wax		10 ~ 20%
Anti Oxidant	6683-19-8	0.5~2%
Hazardous ingredients	None	

## 4. First Aid Measures

Ingestion	Seek medical attention immediately.
Inhalation	If symptomatic, move to fresh air. Get medical attention if symptoms persist.
Skin Contact	Immediately flush skin with large amounts of cold/ice water for at least 30 minutes.  DO NOT ATTEMPT TO REMOVE MOLTEN MATERIAL. Cover affected area with a clean dressing. Seek immediate medical attention.
·	Immediately flush eye with large amounts of cold water for at least 30 minutes. <b>DO NOT ATTEMPT TO REMOVE MOLTEN MATERIAL</b> . Cover affected area with a clean dressing. Seek immediate medical attention.
Most important symptoms and hazardous effects	Redness, swelling, and pain caused by burns.
Protection for first aid personnel	Immediately flush the burned part with large amounts of cold/ice water for at least 30 minutes. <b>DO NOT ATTEMPT TO REMOVE MOLTEN MATERIAL</b> . Cover affected area with a clean dressing. Seek immediate medical attention.
Recommendations to physicians	-



# Material Safety Data Sheet ULTRAMELT 3001

31/05/2018 : Update

5. Fire Fighting Measures
---------------------------

<b>Extinguishing Agents</b>	Water spray, dry chemicals.		
Special fire fighting hazards	None		
	<ol> <li>Use water or dry chemical for fire extinguishing; small-scale of fire can use the way of sprinkling water.</li> <li>Sprinkle the source of ignition with water to lower its temperature.</li> </ol>		
Special Firefighting Procedures	<ol> <li>Sprinkling products in molten state at large-scale fire will causethe splasing of hot water and melting products.</li> <li>It's required to wear protective clothing with a supply of respiratory equipment.</li> <li>After the fire is extinguished, isolation zone should be set up before cooling and curing of the internal products.</li> </ol>		
Special protective equipment of firefighters	Wear self-contained breathing apparatus and protective clothing.		
Explosion bottom line	Explosion upper limit Explosion lower limit	Not applicable Not applicable	

## 6. Accidental Release Measures

·	Avoid contacting the hot melting materials with skin and eyes from getting burns.  In accordance with international conventions or local regulations. Incineration at the
•	government-approved incineration.
Cleaning Method	Use broom and dustpan for cleaning

## 7. Handling And Storage

	Avoid contacting the hot material with the skin. Avoid children from touching.
Storage	Avoid contacting with oxides, exposuring under the sun, and be away from the fire.
Otorage	Stored in sealed containers (to prevent dust pollution)

## 8. Exposure Controls, Personal Protection

Engineering control None				
Control parameters	•			
Time weighted average for an 8	Short Term Exposure	CEILING Biological exposure index (BEI)		
hour shift (TWA)	Limit (STEL)	Biological exposure index (BE		
No data	No data	No data No data		
	Respiratory Protection	Tough the smoke and smell generated by hot melting is not toxic, but due to different feeling of each person, it is recommended to wear a mask.		
Personal protective equipment	Hands protection	Heat insulation gloves		
	Eyes protection	safety goggle		
	Skin protection	Wearing long-sleeved or protective clothing can avoid unexpected burns while using hot melt adhesive.		
Sanitary measures	No specific requirement			



# **Material Safety Data Sheet**

# **ULTRAMELT 3001**

31/05/2018 : Update

9. Physical And Chemical Prope	erties
--------------------------------	--------

States of Matter	solid	Odor	resin
Olfactory threshold	No applicable	Melting point	No applicable
РН	No applicable	Boiling Point	No applicable
Flash point	over 392°F,200°C	Flammability (solid, liquid)	No applicable
Test method	■open cup □ closed cup	Decomposition temperature	_
Auto-ignition temperature	No applicable	Explosion limit	No applicable
Specific Gravity	0.92 ~ 0.98	Solubility	No applicable
Evaporation Rate	No applicable	octanol / water partition coefficient (log Kow)	No applicable
Shape	Granule or Pellet	Color	White
Soften Point	110 ± 5℃	Viscosity(180°C)	710 ~ 1,070cps

## 10. Stability And Reactivity

Stability	Stable	
Special Conditions Of		
Hazardous Reaction	Not applicable	
Conditions to Avoid	Temperature above 200°C	
Incompatibility	might react with strong oxidant	
Hazardous Decomposition	Flammable Hydrocarbon, carbon monoxide and fumes.	
Products		

## 11. Toxicological Information

Exposure approach	None	
Symptoms	None	
Acute Toxicity	Inhalation	Inhalation of dust and smoke will stimulate the respiratory system.
	Skin	None
	Eye	None
	LD50(testing animal's absorption approach)	No data
	LC50(testing animal's absorption approach)	No data
	500mg/24hr(rabbit, skin)	No data
	20mg/24hr(rabbit, eyes)	No data
chronic toxicity or long-term	None	

# 12. Ecological Information

EcologicalToxicity	LC50(fish)	No data	
	EC50(aquatic invertebrates)	No data	
Sustainable and De-toxic	Difficult to naturally degrade, but can be recycled by appropriate ways		
Ecologic Accumulation	No data		
Liquidity in Soil	No data		
Other poor Effect	Improper burning may generate hazardous gas.		



# Material Safety Data Sheet ULTRAMELT 3001

31/05/2018 : Update

#### 13. Disposal Considerations

	Refer to relevant regulations
Disposal considerations	Storage waste according to storage conditions
	3. Able to apply specific incineration or sanitary land filling

### 14. Transportation Information

14. Hansportation information	
The United Nations	None
The United Nations Shipping	None
D.O.T. Hazard Class	None
Package Category	None
Maritime Pollutants(yes/no)	No
International Transport	Not regulated
Domestic Transport Regulation	Not regulated
Special Transport Way And	Not regulated

#### 15. Regulatory Information

1. Rules of labor safety and health facilities

Contact No

2. Rules on Hazard Communication of Dangerous Materials and Toxic Materials'

0408 612 556

- 3. Organic solvent poisoning prevention regulation
- 4. Standards of Permissible Exposure Limits of Airborne Hazardous Substances in Workplace
- 5. Road Traffic Safety Regulation
- 6. Methods and Facilities Standards for the Storage, Clearance and Disposal of Industrial Waste
- 7. Public Hazardous Substances & Flammable Pressurized Gases Establishment Standards & Safety Control Regulation.

#### 16. Other Information

NFPA CODE	Health Hazard	1
	Fire Hazard	1
	Reactivity Hazard	0
	Specific Hazard	None
		_
Prepared Company	Nordale Australia Pty Ltd	
Company Telephone	1300 550 377 / 03 9357 7100	
Contact Person	Graham Prisk	